



Cobrex® Instantaneous Steam Water Heater

Performance by Model Number

120°F Domestic Hot Water Delivered

5 PSI INLET STEAM PRESSURE

Model No.	GPM Delivered (40°F to 120°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 120-20-5	20	5	1	833	800	1-1/4	7 psi
CCX 120-30-5	30	5	1	1250	1200	1-1/2	
CCX 120-40-5	40	5	3	1667	1600	1-1/2	
CCX 120-50-5	50	5	3	2083	2000	2	
CCX 120-60-5	60	5	3	2500	2400	2	
CCX 120-75-5	75	5	5	3125	3000	2	10 psi
CCX 120-90-5	90	5	6	3750	3600	2 (2 ea.)	
CCX 120-120-5	120	5	6	5000	4800	2 (2 ea.)	15 psi

10 PSI INLET STEAM PRESSURE

Model No.	GPM Delivered (40°F to 120°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 120-20-10	20	10	1	840	800	1-1/4	7 psi
CCX 120-30-10	30	10	1	1259	1200	1-1/2	
CCX 120-40-10	40	10	3	1679	1600	1-1/2	
CCX 120-50-10	50	10	3	2099	2000	1-1/2	
CCX 120-60-10	60	10	3	2518	2400	2	
CCX 120-75-10	75	10	5	3148	3000	2	10 psi
CCX 120-90-10	90	10	6	3777	3600	1-1/2 (2 ea.)	
CCX 120-120-10	120	10	6	5036	4800	2 (2 ea.)	15 psi

15 PSI INLET STEAM PRESSURE

Model No.	GPM Delivered (40°F to 120°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 120-20-15	20	15	1	847	800	3/4	7 psi
CCX 120-30-15	30	15	1	1268	1200	1-1/2	
CCX 120-40-15	40	15	3	1691	1600	1-1/2	
CCX 120-50-15	50	15	3	2114	2000	1-1/2	
CCX 120-60-15	60	15	3	2537	2400	1-1/2	
CCX 120-75-15	75	15	5	3171	3000	2	10 psi
CCX 120-90-15	90	15	6	3805	3600	1-1/2 (2 ea.)	
CCX 120-120-15	120	15	6	5073	4800	1-1/2 (2 ea.)	15 psi