



## CSX Single Configuration when Producing 120°F Domestic Water from various supply steam pressures

	MODEL No.	Domestic Water Temperature °F	Domestic Water Delivered (gpm)	Steam Pressure Supplied (psi)	MBtu/h Input	Steam Flow in HX (lb /hr)	Product Configuration	Steam Valve	Condensate Trap NPT
<b>STEAM VALVE NOT REQUIRED</b>	CSX-120-15-5	120	15	5	600	624	A	none	1-1/4
	CSX-120-30-5	120	30	5	1200	1249	A	none	1-1/2
	CSX-120-45-5	120	45	5	1800	1873	B	none	2
	CSX-120-60-5	120	60	5	2400	2497	C	none	2
	CSX-120-75-5	120	75	5	3000	3121	C	none	2
	CSX-120-15-10	120	15	10	600	630	A	none	1-1/4
	CSX-120-30-10	120	30	10	1200	1259	A	none	1-1/2
	CSX-120-45-10	120	45	10	1800	1889	B	none	2
	CSX-120-60-10	120	60	10	2400	2519	C	none	2
	CSX-120-75-10	120	75	10	3000	3147	C	none	2
	CSX-120-15-15	120	15	15	600	634	A	none	3/4
	CSX-120-30-15	120	30	15	1200	1269	A	none	1-1/2
	CSX-120-45-15	120	45	15	1800	1903	A	none	1-1/2
CSX-120-60-15	120	60	15	2400	2537	B	none	2	
CSX-120-75-15	120	75	15	3000	3175	C	none	2	
<b>PRESSURE REDUCING VALVE REQUIRED</b>	CSX-120-15-30	120	15	30	600	634	A	1	3/4
	CSX-120-30-30	120	30	30	1200	1269	A	1-1/4	1-1/2
	CSX-120-45-30	120	45	30	1800	1903	A	2	1-1/2
	CSX-120-60-30	120	60	30	2400	2537	B	2	2
	CSX-120-75-30	120	75	30	3000	3175	C	3	2
	CSX-120-15-50	120	15	50	600	634	A	3/4	3/4
	CSX-120-30-50	120	30	50	1200	1269	A	1-1/4	1-1/2
	CSX-120-45-50	120	45	50	1800	1903	A	1-1/2	1-1/2
	CSX-120-60-50	120	60	50	2400	2537	B	2	2
	CSX-120-75-50	120	75	50	3000	3175	C	2-1/2	2
	CSX-120-15-150	120	15	150	600	634	A	1/2	3/4
	CSX-120-30-150	120	30	150	1200	1269	A	3/4	1-1/2
	CSX-120-45-150	120	45	150	1800	1903	A	3/4	1-1/2
CSX-120-60-150	120	60	150	2400	2537	B	1	2	
CSX-120-75-150	120	75	150	3680	3175	C	1-1/4	2	