



## CSX Single Configuration when Producing 160°F Domestic Water from various supply steam pressures

	MODEL No.	Domestic Water Temperature °F	Domestic Water Delivered (gpm)	Steam Pressure Supplied (psi)	MBtu/h Input	Steam Flow in HX (lb /hr)	Product Configuration	Steam Valve	Condensate Trap NPT
<b>STEAM VALVE NOT REQUIRED</b>	CSX-160-15-5	160	15	5	900	937	A	none	1-1/2
	CSX-160-30-5	160	30	5	1800	1873	C	none	2
	CSX-160-15-10	160	15	10	900	945	A	none	1-1/2
	CSX-160-30-10	160	30	10	1800	1889	B	none	2
	CSX-160-15-15	160	15	15	900	951	A	none	1-1/2
	CSX-160-30-15	160	30	15	1800	1903	B	none	1-1/2
	CSX-160-45-15	160	45	15	2700	2854	C	none	2
<b>PRESSURE REDUCING VALVE REQUIRED</b>	CSX-160-15-30	160	15	30	900	951	A	1-1/4	1-1/2
	CSX-160-30-30	160	30	30	1800	1903	B	2	1-1/2
	CSX-160-45-30	160	45	30	2700	2854	C	2	2
	CSX-160-15-50	160	15	50	900	951	A	1-1/4	1-1/2
	CSX-160-30-50	160	30	50	1800	1903	B	1-1/2	1-1/2
	CSX-160-45-50	160	45	50	2700	2854	C	2	2
	CSX-160-15-150	160	15	150	900	951	A	3/4	1-1/2
	CSX-160-30-150	160	30	150	1800	1903	B	3/4	1-1/2
CSX-160-45-150	160	45	150	2700	2854	C	1-1/4	2	