

# Maxim® Low NOx Packaged Water Heater

AquaPLEX® Duplex Stainless Steel

## Standard Features and Equipment

### Performance

- 80.5% to 81.9% thermal efficiency
- NOx emissions < 55 ppm (199 to 399 MBH)

### Pressure Vessel

- AquaPLEX tank (unlined duplex stainless steel)
- ASME stamped and National Board Registered for 150 psi maximum allowable working pressure
- Temperature and pressure relief valve (ASME rated)
- Non-ferrous, removable tank fittings
- Inspection opening/cleanout
- Fiberglass insulation
- Coated steel jacket panels
- Drain valve
- Tie down anchor points on tank

### Heat Exchanger

- AquaPLEX fire tubes with baffles
- SCALEGUARD® tube sheet protection

### Burner, Operating and Safety Controls

- Power combustion burner
- Spark ignition
- Electronic flame safeguard with pre-purge
- Dual operating thermostats (adjustable 75° to 180°F)
- High-temperature limit
- Terminals for remote on-off

### Warranty and Service Policy

- 15-year tank warranty (PV902)<sup>1</sup>
- 1-year burner and parts warranty (PV536)<sup>1</sup>
- 1-year cost-free service policy (PV551)<sup>1</sup>
- Conditions exist outside of the continental United States

### Codes and Standards

- Intertek/ETL listed
  - UL 732 / UL 795
  - NSF 372 lead free
- ASHRAE 90.1 compliant

### Miscellaneous

- Barometric damper
- Factory-authorized startup

<sup>1</sup>See complete warranty and service policy for full details

PVI reserves the right to change the design and specification without notice.

## Factory Options Packages

### 1 Accessories Package

- Electronic low-water cutoff (test and manual reset)
- High temperature limit (manual reset)
- Relay and proving terminal for remote equipment

### 2 Digital Temperature Control Package

- Electronic operating control with digital readouts
- Tank pressure gauge at drain valve connection

### 3 Alarm and Communications Package

(Includes "Digital Temperature Control Package")

- Alarm on any failure functionality with switched contacts for remote notification
- 95dB local audible alarm with silencing switch
- 485 serial cable to connect electronic operator to BAS (Modbus RTU)

### Factory Installed Individual Options

- A** CSA-rated temperature and pressure relief valve(s)
- C** MASS code compliance

### Field Installed Options

(Ordered as a line item)

- Protocol gateways (consult factory)
  - Bacnet MSTP
- Direct combustion air intake adapter for burner

### Optional Service Policy

Long-life service policy (PV559)<sup>1</sup>

*Conditions exist outside of the continental United States*

### Custom Configuration

Consult representative for additional custom options

### Part Number Sequence

Base Model# + "Packages" + "Options"

Example: 40 L 250 AMXS-13A



Hot Water Solutions



A WATTS Brand

PVI Industries • Fort Worth, TX

USA: T: (817) 335-9531 • Toll Free: (800) 784-8326 • PVI.com

Technical Support • (800) 433-5654 • Mon-Fri, 8 am - 5 pm CST/CDT

© 2024 PVI