

AquaPLEX® Storage Tanks

Unlined Duplex Alloy, Horizontal Storage



STANDARD FEATURES and EQUIPMENT

PRESSURE VESSEL

- ASME stamped and National Board Registered for 150 psi MAWP
- Nonferrous removable fittings at all tank connections
- Lifting lugs
- Removable end head ≤ 250 gallons
- Manway tank access > 250 gallons
- Painted steel base skid
- Fiberglass insulation
- Coated steel jacket panels
- Tie down anchor points on tank
- Bottom drain valve
- Flow diffuser installed on circulation return

WARRANTY and SERVICE POLICY

- 25-year tank warranty (PV901) ①

CODES AND STANDARDS

- ASHRAE 90.1 compliant
- Intertek / ETL listed NSF372 lead-free

① See complete warranties and service policies for full details.

PVI reserves the right to change the design and specification without notice.

PART NUMBERS SEQUENCE

PN	Model
144317	LH 150 ATR
144318	LH 175 ATR
144319	LH 215 ATR
144245	LH 250 ATR
144222	LH 300 ATR
144320	LH 400 ATR
144225	LH 500 ATR
144321	LH 600 ATR
144228	LH 750 ATR
144322	LH 900 ATR
144323	LH 1000 ATR
144231	LH 1250 ATR
144246	LH 1500 ATR

FIELD INSTALLED OPTIONS (Ordered as a line item)

- Tank thermostat with 3/4" well (PN 128516)
- Relief Valve Kit 1-inch 150 psi (PN 102563)
- Installation kit 150-400 gallon (PN 143406)
- Installation kit 500-1500 gallon (PN 143407)

OPTIONAL SERVICE POLICY

- Long-life service policy (PV559) ①
Conditions exist outside of the continental United States

CUSTOM CONFIGURATION

Consult representative for all additional custom options



PVI Industries, LLC
Fort Worth, TX • (800) 784-8326 • www.pvi.com