

# AquaPLEX® Storage Tanks

## Unlined Duplex Alloy, Vertical Storage



### **STANDARD FEATURES and EQUIPMENT**

#### **PRESSURE VESSEL**

- ASME stamped and National Board Registered for 150 psi MAWP
- Nonferrous removable fittings at all tank connections
- Lifting lugs
- Removable top head < 250 gallons
- Manway tank access ≥ 250 gallons
- Steel base skid
- Fiberglass insulation
- Coated steel jacket panels
- Tie down anchor points on tank
- Bottom drain valve

#### **WARRANTY and SERVICE POLICY**

- 25-year tank warranty (PV901) ①

#### **CODES AND STANDARDS**

- ASHRAE 90.1 compliant
- Intertek / ETL listed NSF372 lead-free

① See complete warranties and service policies for full details.

PVI reserves the right to change the design and specification without notice.

### **PART NUMBERS SEQUENCE**

Base PN	PN W/Flow Diffusers	Model
135747	135957	L 125 ATR
135674	135955	L 150 ATR
135673	135953	L 175 ATR
135615	135950	L 215 ATR
132619	135945	L 250 ATR
135787	135960	L 300 ATR
135792	135963	L 400 ATR
135806	135965	L 500 ATR
135836	135968	L 600 ATR
135895	135970	L 750 ATR
135898	135973	L 900 ATR
138032	138034	L 1000 ATR
138030	138033	L 1250 ATR
135899	135975	L 1500 ATR

### **FIELD INSTALLED OPTIONS** (Ordered as a line item)

- Tank thermostat with 3/4" well (PN 128516)
- Relief Valve Kit 1-inch 150 psi (PN 102563)
- Installation kit 125-400 gallon (PN 143406)
- Installation kit 500-3000 gallon (PN 143407)

### **OPTIONAL SERVICE POLICY**

- Long-life service policy (PV559) ①  
Conditions exist outside of the continental United States

### **CUSTOM CONFIGURATION**

Consult representative for all additional custom option



PVI Industries, LLC  
Fort Worth, TX • (800) 784-8326 • www.pvi.com